

APS15 SERIES ALL-PURPOSE SEEDERS

HP REQUIRED
25-130 HP

HITCH
Cat. 1 & 2



SEEDERS


The seeder that does it all.

The APS15 is at home in freshly prepared soil or overseeding existing turf. The front spike rollers break up the soil crust or penetrate the thatch to disturb the right amount of soil. The seed is dropped, protected from the wind by a shield, allowing it to drop to the ground where it is gently pressed into the soil by the notched or spiked rear roller. The initial seed-to-soil contact is essential to achieving a high germination rate.

The All-Purpose Seeder is ground driven with no driveline and related drivetrain components to maintain. By adjusting the front two rollers, you can control how aggressive you want to be in the area you are seeding or overseeding.

The many uses for the APS:

- Bare dirt seeding
- Turf overseeding
- Wildlife Conservation Seeding



Choose between a rear spiked roller or a 12" cast packer wheel roller.



Optional small seeds box.

	APS1548	APS1560	APS1572	APS1586
Horsepower	25-130 HP			
Hitch	Cat. 1			Cat. 1 & 2
Working Width (cm)	50" (127)	60" (152)	72" (183)	86" (218)
Overall Width	60"	72"	81"	98"
Overall Length	49"	51"	52"	55-1/2"
Overall Height	42-1/2"			
Weight - lb (kg)	547 (248)	702 (318)	836 (379)	1,070 (485)
Seedbox Capacity	4	5	6	7.2 Bushel
Output Range	Varies By Seed Variety; Consult Manual			
Front Roller - 2	8" Diameter, 1" Spindles w/Greaseable Ball Bearings			
Rear Roller	8" Diameter w/Studs or 12" Cast Packer Wheels			
Chain	#40 with Spring Loaded Idler			
Seed Cups	7	8	10	12
Front Roller Angling	Up to 20°			
Roller Studs	1/2" to 2" Heat Treated Steel, Replaceable			
Transport Lights	Standard			
Color				

*60" and 86" models with rear cast packer wheels

